

METHOD, SYSTEM, PROGRAM, AND STORAGE CARTRIDGE
FOR STORING DATA IN A STORAGE MEDIUM

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

[0001] The present invention relates to a method, system, program, and storage cartridge for storing data in a storage medium.

2. Description of the Related Art

10 [0002] Three prevalent tape storage technologies include a helical scan tape where data is stored along vertical or diagonal tracks on the tape, parallel tape where data is stored on tracks in parallel during one scan on the tape, and serpentine tape where data is written in a forward and then reverse direction in a serpentine pattern across bands or tracks on the magnetic tape medium. In serpentine tape drives, the bands
15 extending the length of the tape may be divided into sections, such as a housekeeping section, calibration section, user data section, etc., where data is written in a serpentine manner within the longitudinal bands of a section. A serpentine tape drive first read/writes a track in a forward direction within a section of a band, referred to as a wrap, then read/writes the next track in a reverse direction, and so on,
20 leading to a serpentine pattern for the data layout. In tape technology, a wrap comprises one of the bands that extend the entire length of the tape and a wrap section comprises a section of the wrap.

[0003] FIG. 1 illustrates a layout of a tape format in conformance with the Linear Tape Open (LTO) Ultrium format, which is a serpentine tape format technology. The
25 length of the tape is divided into logical points (LPs), which define bounds of regions of the tape. The regions of LP0 to LP1 and LP6 and LP7 are unused as they are at the beginning and end of the tape, the region of LP1 to LP2 is a servo acquisition area, LP2 to LP3 is a calibration area that includes different information in the different

T09080" 665E2660

bands, LP3 to LP4 is the user data, LP4 to LP5 is an unused user data area and LP5 to LP6 is a servo acquisition region for reverse wraps. The user data section further includes a format identification data set (FID), including information regarding the format of the tape and the tape drive that wrote the FID. In the LTO format, data is written in a serpentine fashion between the logical points each of the data sections between LP3 and LP4.

[0004] The access time for a tape drive comprises the time from when the host attachment's input/output (I/O) request is submitted to when the operation is complete. For a Space or Locate command the data should then be in buffer, for a Read command the data has been transferred back to the host. The overall access includes two components: the lateral access and the longitudinal access. Longitudinally every wrap (from LP3 to LP4) may be divided into multiple pieces. In LTO each wrap is divided into two pieces (at the mid-point), each of which is called a wrap section. Laterally data is divided into bands (e.g. the LTO format has 4 data bands), and at any given location there are generally as many wrap sections which can be accessed via lateral movement alone as there are wraps (e.g. there are only 48 wrap sections available via lateral access at any given longitudinal position in LTO, one corresponding to each of the 48 wrap positions, even though there are a total of 96 wrap sections because each of the wraps is longitudinally divided into two wrap sections). Lateral access involves moving the head laterally to the proper wrap, and is limited to approximately 9 mm in the worst case in LTO. Longitudinal access involves moving the tape until the target is either under the head or in buffer. In LTO, if the head begins in the same tape half as the target the maximum required longitudinal access is 290 meters (e.g. BOT to (LP3+LP4)/2), but if the head begins in the opposite tape half it could be as much as 580 m (e.g. BOT to LP4).

[0005] To determine the longitudinal position, the tape drive uses the Tape Directory which is stored either on tape or in some auxiliary cartridge memory (e.g. LTO's CM). The tape directory will typically include information at different

longitudinal positions on tape which can be used at a minimum to bound the target (e.g. if we know there is one Filemark in a full wrap section all that is known is that the Filemark is between two points such as between LP3 and $(LP3+LP4)/2$ if it is in the first wrap section). The information to bound the target can also be used in linear interpolation to estimate the target's position (e.g. if we know there are 1 million 1Kbyte records in a wrap section, then interpolation would suggest that the 400,000th record is approximately 40% of the way between the beginning and end of that wrap section).

[0006] One drawback to the relatively inexpensive tape storage is the time required to access data. In fact, the time to wind the tape to the correct longitudinal position can take a minute or more. Thus, the tape access time is primarily determined by the time needed to longitudinally wind the tape to the correct position.

[0007] Data may be accessed randomly from the tape. When randomly accessing data, the tape drive may have to wind the tape to entirely different longitudinal positions within the user data area, e.g., the area between LP3 to LP4. The longer the user data area or tape length, the more time required to wind or position the tape medium under the tape head.

[0008] Thus, there is a need in the art to provide improved techniques for optimizing access time when randomly accessing data on a tape storage medium.

SUMMARY OF THE PREFERRED EMBODIMENTS

[0009] Provided is a method, system, and program for storing data in a storage medium. A layout of a storage medium including a first and second user data sections is provided, wherein the first user data section comprises a faster access storage space than the second user data section. A determination is made of a first set of data to be accessed at a faster rate than a second set of data. The first set of data is written to the

first user data section and the second set of data is written to the second user data section.

[0010] In further implementations, the storage medium comprises a magnetic tape medium and the first user data section has a shorter longitudinal length than the
5 second user data section. Still further, the data may be written in separate serpentine patterns within the first and second user data sections.

[0011] Further provided is a method for storing data records on a magnetic tape medium. a first set of data records is selected to write to a first user data section of the magnetic tape medium. The magnetic tape medium further includes a second user
10 data section, wherein the first user data section comprises a faster access user data section than the second user data section. The first set of data records are transferred to write to the magnetic tape medium wherein the first set of data records are written to the first user data section. The second set of user data records are transferred to write to the magnetic tape medium after writing the first set of data records. The
15 second set of data records are written to one of the first user data section or second user data section of the magnetic tape medium.

[0012] Still further provided is a magnetic tape medium, wherein the magnetic tape medium comprises a first user data section and a second user data section. The first user data section comprises a faster access storage space than the second user data
20 section. A first set of data to be written at a faster rate than a second set of data is written to the first user data section and the second set of data is written to the second user data section.

[0013] The described implementations provide a technique to implement a fast access data section within a storage medium, such as a magnetic tape medium, to
25 allow faster random access to data in the fast access data section over data stored in one or more additional user data sections on the storage medium.

T09080" 665E2660

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] Referring now to the drawings in which like reference numbers represent corresponding parts throughout:

FIG. 1 illustrates the layout of a magnetic tape medium in a manner known in the prior art;

FIG. 2 illustrates tape storage system in which aspects of the invention are implemented;

FIG. 3 illustrates the layout of a magnetic tape medium in accordance with implementations of the invention;

FIG. 4 illustrates a tape cartridge memory used in accordance with implementations of the invention;

FIG. 5 illustrates logic implemented in a tape drive to access data on a magnetic storage medium in accordance with implementations of the invention; and

FIGs. 6 and 7 explain serpentine patterns for writing data to wrap sections in accordance with implementations of the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0015] In the following description, reference is made to the accompanying drawings which form a part hereof and which illustrate several embodiments of the present invention. It is understood that other embodiments may be utilized and structural and operational changes may be made without departing from the scope of the present invention.

[0016] FIG. 2 illustrates an architecture of a tape storage system in which aspects of the invention are implemented. A tape cartridge 2 includes a high capacity single reel of magnetic tape 4 and a non-volatile read/writable cartridge memory 6 which maintains information about the format and layout of data on the magnetic tape. In further implementations, the tape cartridge 2 may comprise a dual wheel tape cartridge. In certain implementations, the tape cartridge 2, includes aspects of the

Linear Tape Open (LTO) Ultrium format. Details of the Ultrium format are described in the publication "Data Interchange on 12,7 mm 384-Track Magnetic Tape Cartridges – Ultrium-1 Format", Draft Standard published by the ECMA (March 2001), which publication is incorporated herein by reference in its entirety.

- 5 **[0017]** The tape cartridge 2 may be inserted in a tape drive 10, that includes read/write heads (not shown) capable of transferring data to and from the magnetic tape 4 in a manner known in the art. The tape drive 10 further includes one or more tape drive controllers 12 that receive Input/Output (I/O) requests from a host system 20 and is capable of executing the received I/O requests by rewinding the tape and
- 10 positioning the tape heads at a particular location on the magnetic tape 4 using tape drive mechanisms and algorithms to estimate the likely location of a file on the magnet tape 4 in a manner known in the art. The tape drive 10 may be enclosed within the host system 20 or as a standalone unit or in a tape library (not shown). The tape drive 10 may connect with the host 20 through a direct interface, e.g., SCSI,
- 15 Fibre Channel, etc., such as the case if the tape drive 10 is connected to the host 20 or connect over a network, such as a Local Area Network (LAN), Storage Area Network (SAN), Wide Area Network (WAN), the Internet, an Intranet, etc.
- [0018]** The host 20 includes a host application 22, which may comprise a backup program, that transfers data to the tape drive 10 to sequentially write to the magnetic
- 20 tape 4. The host application 22 may utilize the Small Computer System Interface (SCSI) tape commands to communicate I/O requests to the tape drive 10. Details of the SCSI commands used to communicate I/O requests between the tape drive 10 and host application 22 are described in the publications "StorageSmart by IBM: Ultrium Tape Drive: SCSI Reference", published by International Business Machines
- 25 Corporation ("IBM) as document no. WB1110-00 (August, 2000) and "SCSI-3 Stream Commands (SSC)", published by the American Standards Institute as Working Draft, Revision 22 (Jan. 1, 2000), which publications are both incorporated herein by reference in their entirety.

TUC920000097US1

5 [0019] In accordance with SCSI tape commands, the host application 22 would write data records sequentially to the tape drive 20. To retrieve data records, the host application 22 would read data sequentially from the magnetic tape 20. To access data randomly from the magnetic tape 4, the host application 22 could send the SCSI
10 SPACE and LOCATE commands to the tape drive 20 to request a data record at an offset from the last record read from the magnetic tape 4. The host application 22 would use the SPACE command to instruct the tape drive 10 to set a new logical position relative to the current logical position, which is determined from the last data record returned by the tape drive 10. The SPACE command specifies a count field
15 indicating the number of blocks (or filemarks) to move forward (if positive) or backward (if negative). The host application 22 would use the LOCATE command to instruct the tape drive 10 to position the magnetic tape 4 to the specified logical element at the specified position.

20 [0020] FIG. 3 illustrates a layout format of the logical points on the magnetic tape 4 in accordance with one implementation of the invention. The layout of FIG. 3 includes sections found in the prior art LTO tape format, such as the housekeeping sections from LP1 to LP2, and the beginning (LP0 to LP1) and end (LP6 to LP7) sections. The layout of FIG. 3 further includes two separate user data sections 50 and 52, extending from LP3 to LP4 and LP3' to LP4', respectively. Data section 50 has a
25 length that is less than the length of data section 52. Because data section 50 has a shorter longitudinal length, less time is needed to seek to a location in data section 50 during a random access operation than the time required to seek to a location in the longer data section 52. Thus, data section 50 comprises a faster data access section where the host application 22 can place data accessed more frequently, such as control
and configuration data, application data, directory information, and other more frequently accessed data. Further, because the first user data section 50 is located before the second user data section 52 on the tape, data in the first user data section 50

may be accessed faster than data in the second user data section 52 when seeking from the beginning of the tape.

[0021] In the prior art LTO tape format, shown in FIG. 1, each wrap extending between LP3 and LP4 in FIG. 1 would include two wrap sections of equal length. In the prior art layout of FIG. 1, the user data section between LP3 and LP4 has four bands, where each band includes six forward wraps extending from LP3 to LP4 and another six backward wraps extending from LP4 to LP3. Because each wrap includes two wrap sections, there are a total of 96 wrap sections in the user data section between LP3 and LP4 in the prior art tape layout arrangement.

[0022] In one implementation, each of the data sections 50 and 52 include separate serpentine wraps, where each of the four bands has six forward wraps and six backward wraps. In the described implementations, each of the 48 wraps in the data sections 50 and 52 would comprise wrap sections. In this way, 96 wrap sections are equally divided between the two user data sections 50 and 52, where there is one wrap section for each wrap.

[0023] FIG. 4 illustrates further details of the data structures in the cartridge memory 6, including initialization data indicating the longitudinal position of all the logical points, including LP1, LP2, LP3, LP4, LP3', LP4', LP5, LP6, and LP7. The tape drive controller 12 would use the initialization data 70 to determine the start and end of each of the user data sections 50 and 52. The cartridge memory 6 further includes a table directory 72 that includes entries for each of the wrap sections. As discussed, in implementations where there are two separate user data sections 50 and 52, the 96 possible wrap sections would be divided between these two user data sections. Thus, each wrap in the user data sections 50 and 52 would comprise a wrap section. For each of the wrap sections listed in the table directory 72, the wrap section entry may specify:

Data Set ID: specifies the Data Set Identity of the last Data Set written in this wrap section. If this wrap section does not contain valid Data Sets, then this field shall be set to (0x0FFFFFFFFF).

5 Record Count: If this Wrap Section is valid, this field shall contain the number of Records that are started in the current Wrap Section. If the Data Set ID of this Wrap Section is (0x0FFFFFFFFF) and hence this Wrap Section is invalid, the Record Count field is not defined for interchange.

10 File Mark Count: If this Wrap Section is valid, this field shall contain the number of File Marks that are within the current Wrap Section. If the Data Set ID of this Wrap Section is (0x0FFFFFFFFF) and hence this Wrap Section is invalid, the File Mark Count field is not defined for interchange.

CRC: This field shall specify the CRC generated for the wrap section data in the table directory 72.

15 [0024] Additional or different fields may be maintained for wrap sections in the table directory 72 to those described above.

20 [0025] The wrap sections would map to the lateral bands extending through the user data sections 50 and 52 in a predefined manner, such that the wrap sections comprise the forward and backward wraps within the data sections 50 and 52. The tape drive controller 12 would utilize the wrap section information in the table directory 72 to estimate the longitudinal position within the wrap section of a requested data record.

25 [0026] In one implementation, the prior art LTO tape layout format of FIG. 1 may be modified to format the tape layout format of the described implementations of FIG. 3. For such implementations, to define the second user data section 52, LP3' may be set to a fixed value, such as 0.50 meters beyond LP4 so long as LP3' is less than LP5. The LP5 point in the prior art LTO Ultrium format (FIG. 1) then becomes LP4', and LP3 to LP5 can be 580 meters on a Type A LTO cartridge. Thus, if LP4 is set to LP3 plus 79.5 meters, then LP3 plus 79.5 meters plus 0.5 meters equals LP3 plus 80

T 09030" 6652660

5 LP3 and LP5.

10 accessing the cartridge, so that only tape drives 10 that include logic capable of
writing to the different user data sections 50 and 52 would access the magnetic tape
medium 4.

15 controller 12 receiving I/O commands from the host 20 to reposition the magnetic tape 4 to a new position and read or write data records from that new position. The host application 22 may use the SCSI LOCATE or SPACE command to instruct the tape drive 10 to move the magnetic tape 4 to a new position. The tape drive controller 12 then processes (at block 102) the table directory 72 to determine the
20 wrap section number n and to estimate the offset therein of the requested data set in a manner known in the art.

25 108) the magnetic tape 4 the determined longitudinal offset within wrap n of the user data section 50. As discussed, when the user data sections is divided into two sections 50 and 52, the wrap section n number corresponds directly to a forward or backward wrap number within one of the bands. The tape drive controller 12 then

accesses (at block 110) the requested data set from the tape after winding to position the requested data set under the read/write head of the tape drive 10 and executes the I/O request at the accessed data set. If (at block 106) the wrap section number n in the second user data section 52, then the tape drive controller 12 winds (at block 112) the magnetic tape 4 to the determined longitudinal offset of wrap n within the second user data section 52.

[0030] In the described implementations, data is written in a serpentine pattern through the user data sections 50 and 52. FIG. 6 provides a table explaining how data is written in a serpentine pattern in wrap sections through user data sections 50 and 52 in one implementation. In the serpentine pattern of FIG. 6, the first 48 wrap sections, 0-47, alternate writing forward and backward between LP3 and LP4, ending on LP3 in the 48th wrap section (wrap section 47). The next 48 wrap sections are then written in the same serpentine pattern between LP3' and LP4', alternating between forward and backward, and ending on LP3'. With the serpentine pattern implementation of FIG. 6, the tape drive must seek from LP3 to LP3', which as described above may be 80 meters apart, at the end of the first user data section 50 to the beginning of the second user data section 52.

[0031] FIG. 7 illustrates an additional serpentine pattern implementation that minimizes the distance to seek when writing data to the 49th wrap section (wrap section 48). In the serpentine pattern of FIG. 7, the tape drive writes in a serpentine pattern, alternating in the forward and backward direction between LP3 and LP4 for the first 47 wrap sections, e.g., wrap sections 0 through 46, which is the same pattern in FIG. 6 for the first 47 wrap sections. However, the pattern of FIG. 7 differs from FIG. 6 in that upon reaching the end of the 47th wrap section (the end of wrap section 46), the tape drive moves from LP4 to LP3' and then starts writing in a serpentine pattern, alternating between the forward and backward direction between LP3' and LP4' in the second user data section 52. This alternating pattern continues from wrap sections 48 through 94. There is a last possible wrap section 95, which can be written

[illegible]

- 5 [0032] The serpentine pattern of FIG. 7 improves the write performance when writing to wrap sections between the first 50 and second 52 user data sections by avoiding the need to seek from LP3 to LP3' when starting to write wrap section 48 at the beginning of the second user data section 52. Instead, with the serpentine pattern of FIG. 7, the tape drive needs only seek 0.5 meters when moving from the end of the first user data section 50 to the beginning of the second user data section 52. This is a performance improvement over the serpentine pattern of FIG. 6, which requires that the tape drive seek 80 meters when moving from the end of the first user data section 50 to the beginning of the second user data section 52.
- 10 [0033] Because the second user data section 52 is at a length of tape that is beyond the first user data section 50, the seek time from the beginning of the tape takes longer. Because the user data section 50 is shorter than is the user data section 52, the average seek time from one point in user data section 50 to another in user data section 50 is shorter than from one point in user data section 52 to another point in user data section 52. Thus, from the beginning of the tape or for movements within a wrap section, the first user data section 50 is faster than the second section 52 because the second section 52 follows the first 50, and the first section is shorter. Accordingly, data that is more frequently accessed could be placed in the faster access first user data section 52.
- 20 [0034] In certain implementations, the host application 22 may include logic to organize data records for storage to the magnetic tape 20 to place data likely to be accessed more frequently in the first user data section 50 and data likely to be accessed less frequently following the more frequently accessed data. When sequentially writing the data to the magnetic tape 4, the host application 22 would

	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2423	2424	2425	2426	2427	2428	2429	2430	2431	2432	2433	2434	2435	2436	2437	2438	2439	2440	2441	2442	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

- 15

[0036] The preferred embodiments may be implemented as a method, apparatus or article of manufacture using standard programming and/or engineering techniques to produce software, firmware, hardware, or any combination thereof. The term “article of manufacture” as used herein refers to code or logic implemented in hardware logic (e.g., an integrated circuit chip, Field Programmable Gate Array (FPGA), Application Specific Integrated Circuit (ASIC), etc.) or a computer readable medium (e.g., magnetic storage medium (e.g., hard disk drives, floppy disks, tape, etc.), optical storage (CD-ROMs, optical disks, etc.), volatile and non-volatile memory devices (e.g., EEPROMs, ROMs, PROMs, RAMs, DRAMs, SRAMs, firmware, programmable logic, etc.). Code in the computer readable medium is accessed and executed by a processor. The code in which preferred embodiments are implemented may further be accessible through a transmission media or from a file server over a network. In such cases, the article of manufacture in which the code is implemented

may comprise a transmission media, such as a network transmission line, wireless transmission media, signals propagating through space, radio waves, infrared signals, etc. Of course, those skilled in the art will recognize that many modifications may be made to this configuration without departing from the scope of the present invention, and that the article of manufacture may comprise any information bearing medium known in the art.

[0037] In the described implementations, the data is first written to the first user section and after that section fills, to the second user data section. In alternative implementations, data may be written to the second user data section before the first is completely filled. This may be accomplished by predefining a number of blocks, N, in the first section (e.g. 100000 records) and handle it such that a Space or Locate to the N+1 (100001th) Record, or to End of Data (EOD) will position one to the start of the second user data section, from which one can begin writing. Similarly a Space or Locate to block 0, or a Rewind, will position to the start of the first section. In this way, the first user data section could be updated after the second user data sections. Further, the whole serpentine may be processed in the backwards direction in order to start with the end of the second section and work backwards. In such implementations, the first and second user data sections are part of a same logical partition that is still multi-segmented, not multi-partitioned.

[0038] In the described implementations, there were 96 wrap sections equally divided between two different user data sections 50 and 52, where the tape drive controller 12 first writes data in a serpentine pattern to the forward and backward wraps in the first user data section 50 and then, after filling the first user data section 50, writes data in a serpentine pattern to the forward and backward wraps in the second user data section 52. In additional implementations, there may be more than two user data sections, where the initialization data 70 would provide additional logical points for additional user data sections. In such cases, the 96 wrap sections may be divided among the three or more user data sections. Still further, the tape

directory and other page information in the cartridge memory may define additional or fewer wrap sections than the 96 described herein as dispersed among the multiple user data sections.

5 [0039] In the described implementations, data was organized into wrap sections in the user data sections. In alternative implementations, the data in the user data sections may be organized into physically consecutive groups of tracks other than wrap sections.

10 [0040] In the described implementations, the host application 22 communicated with the tape drive 10 using SCSI commands. In alternative implementations, different data transfer protocols other than SCSI may be used.

[0041] FIGs. 6 and 7 illustrate serpentine patterns that may be followed when writing data to wrap sections in the first 50 and second 52 user data sections. However, those skilled in the art will appreciate that different serpentine patterns may be used when writing data to the wrap sections in the user data sections 50 and 52.

15 [0042] In the described implementations, the directory information is stored in cartridge memory. In alternative tape implementations, such as tape cartridges that do not include a cartridge memory device, the directory information may be stored on tape or on a host system.

20 [0043] The described implementations provide a technique for transferring data to a tape drive. Additionally, the above described logic may be used with other input/output (I/O) devices or other storage devices, e.g., optical tape.

25 [0044] The described implementations utilized serpentine Linear Tape Open (LTO) technology. In alternative implementations, alternative tape technologies may be used, such as helical-scan tape drive that read/write vertical or diagonal tracks on the tape using a rotating read/write head and parallel tape drives that read/write tracks in parallel during one scan through the tape. The described implementations may be utilized with Digital Linear Tape (DLT), Quarter Inch Cassette (QIC), Travan, and any other tape technology known in the art.

0992359 080601
T09880 6652660

[0045] The logic implementation of FIG. 5 described specific operations as occurring in a particular order. In alternative implementations, certain of the logic operations may be performed in a different order, modified or removed and still implement preferred embodiments of the present invention. Moreover, steps may be
5 added to the above described logic and still conform to implementations of the invention.

[0046] The foregoing description of the preferred embodiments of the invention has been presented for the purposes of illustration and description. It is not intended to be exhaustive or to limit the invention to the precise form disclosed. Many
10 modifications and variations are possible in light of the above teaching. It is intended that the scope of the invention be limited not by this detailed description, but rather by the claims appended hereto. The above specification, examples and data provide a complete description of the manufacture and use of the composition of the invention. Since many embodiments of the invention can be made without departing from the
15 spirit and scope of the invention, the invention resides in the claims hereinafter appended.

09923599-090604
TUC920000097US1